


# Rugged Mobile PC

# TB-PEM-M10A

- Powered by 12<sup>th</sup> Generation Intel® Core™ i5-1235U/i7-1255U Processor and Windows 11
- Support 16GB RAM + 128GB SSD, the SSD is detachable, easy to expand by simplely pulled out and replaced
- 10.1-inch LCD screen with 700 nits high brightness
- 10-point capacitive touch, support glove touch
- Supports the latest WiFi 6 technology, 4G and Bluetooth 5.1
- 7.4V/5000mAh + 7.4V/700mAh double battery, the large battery is removable and hot-swappable
- Equipped with a full set of interfaces including full-featured Type-C, USB 3.0, Mini HDMI and more
- Choose one of four modules among wired network interface, USB 2.0, RS232 and 2D barcode module, choose as you like
- Passed IP65 and multiple stringent MIL-STD-810G military standard tests, industrial-grade safety protection



12<sup>th</sup> Gen Intel Processors Windows 11







10.1-inch screen

700 nits highlighting


Wi-Fi/BT 5.1/4G



16GB RAM 128GB SSD



Dual battery life



Rich interface expansion



Four-choice module bit



IP65 protection level



## M10ARugged Mobile PC

## BNERU99ed

## Specifications



12<sup>th</sup> Generation Intel<sup>®</sup> Core<sup>™</sup> i5-1235U/i7-1255U Processor





#### Memory

RAM 16GB DDR4L ROM 128GB SSD



Type: LCD Size: 10.1 inch 16:10

Resolution: 1200\*1920 Brightness: 700cd/m<sup>2</sup>



#### **Touch Pannel**

10 points capacity TP G+G Hardness over 7H



289.9\*196.7\*27.4mm 1140g



Power \*1 Volume Key + \*1 Volume Key - \*1 Windows Home \*1 F Key \*1



#### Speaker

Waterproof Speaker \*1



#### **Battery**

7.4V/700mAh(Small Battery) Build in Lithium-ion polymer battery, Non-removable 7.4V/5000mAh (Big Battery) Removable Li-polyment Battery



Wi-Fi 6 802.11a,b,d,e,g,h,i,k,n,r,u,v,w,ac,ax Dual frequency 2.4G+5.8G WIFI





4G



## © GPS

Support: GPS, Beidou, glonass



## N)) Data Collection

NFC Optional, NXP300



#### Adapter

DC 19V 3.42A



#### Rugged Features

MIL-STD-810H: 1.22m drop Working temperature: -20 °C to 60 °C Storage temperature: -30 °C to 70 °C Humidity: 95% Non-Condensing Electrostatic discharge: ± 8kV contact discharge ± 15kV air discharge



### **ৣ** I/O Interface

USB 3.0 \*1 Type C \*1 ∮ 3.5mm \*1 TF/SIM \*1 DC \*1 HDMI mini \*1 12PIN Pogo Pin \*1 Expansion Module: RJ45(10/100M) \*1/RS232 \*1 USB2.0 \*1/QR Code Scanner



